

PRODUCT INFORMATION

SINGLE/DOUBLE DOOR, SURFACE AND FLUSH MOUNT AND STANDARD TYPE MAGNETIC LOCKS



PART No.		
FEM3500(S) FEM3500D(D)	FEM3500M(S) FEM3500DM(D)	FEM3500FM(Old FEM2)
HOLDING FORCE	Up to 280kgs	
VOLTAGE/ CURRENT	Dual Voltage 12/24vDC, 12vDC=490mA 24vDC=245mA	
APPROVALS	4 hour fire rated to A.S. and B.S. standards	
MONITORING	NIL	LP LSS DSS
SIZE	Single door series magnet size: L= 238 x W= 48 x D= 25mm Single door series armature plate size: L= 185 x W= 38 x D= 12mm Single door series DSS-armature plate size: L= 185 x W= 38 x D= 12mm	Double door series surface magnet size: L= 477 x W= 48 x D= 25mm Double door series armature plate size: L= 185 x W= 38 x D= 12mm x 2 pcs Double door series DSS-armature plate size: L= 185 x W= 38 x D= 12mm x 2 pcs
WEIGHT	Single door 2kgs/Double door 4kgs per set	
PACKING PER BOX	Single door 10 per box (21kgs) Double door 6 per box (25kgs)	

Common Features

- ◆ Power-off to release door/s
- ◆ No moving parts
- ◆ Built-in varistor (MOV) surge protection
- ◆ Satin anodised aluminum housing and zinc plated electromagnetic lock body
- ◆ Grain orientated silicone steel armature plates
- ◆ 5 year warranty
- ◆ CE Approved