

PRODUCT INFORMATION

SINGLE/DOUBLE DOOR, SURFACE MOUNT AND STANDARD TYPE MAGNETIC LOCKS



FEM5700 (Old FEM11)

FEM5700D
(Old FEM12)



FEM5700M

NOW WITH
DOOR
POSITION
REED

FEM5700DM

PART No.	
FEM5700 (Old FEM11)(S) FEM5700D (Old FEM12)(D)	FEM5700M(S) FEM5700DM(D)
HOLDING FORCE	Up to 580kgs (for single magnetic lock)
VOLTAGE/ CURRENT	Dual Voltage 12/24vDC, 12vDC=490mA 24vDC=245mA
APPROVALS	4 hour fire rated to A.S. and B.S. standards
MONITORING	NIL LP LSS DSS
SIZE	<p>Single door series magnet size: L= 268 x W= 73 x D= 40mm</p> <p>Single door series armature plate size: L= 190 x W= 61 x D= 16mm</p> <p>Single door series DSS-armature plate size: L= 252 x W= 61 x D= 16mm</p> <p>Double door series surface magnet size: L= 535 x W= 73 x D= 40mm</p> <p>Double door series armature plate size: L= 190 x W= 61 x D= 16mm x 2 pcs</p> <p>Double door series DSS-armature plate size: L= 252 x W= 61 x D= 16mm x 2 pcs</p>
WEIGHT	Single door 4.8kgs/Double door 9.5kgs per set
PACKING PER BOX	Single door 4 per box (19.5kgs) Double door 2 per box (19.5kgs)

Common Features

- ◆ Power-off to release door/s
- ◆ No moving parts
- ◆ Built-in varistor (MOV) surge protection
- ◆ Satin anodised aluminum housing and zinc plated electromagnetic lock body
- ◆ Grain orientated silicone steel armature plates
- ◆ 5 year warranty
- ◆ CE Approved