

PRE Standard Keypad



The PRE (Presco™ Remote Encoder) is designed to be used with the PAC series door access controllers in areas where keypad security is desired, but weather and vandal resistance is not a priority.

When a PRE is coupled with any PAC series door access controller you get the benefits of a secure door access control solution with all of the features of the Presco™ system.



Features

- Compatible with the Presco™ PAC series docders
- Over 19,000,000 possible code combinations
- Audible and visual confirmation of all actions
Sealed tactile buttons
- Available in contrasting colour schemes

Specifications

- Voltage
7-15 Volts D.C current limited to 23mA (supplied by Presco decoder)
- Current
0.25mA in standby
- Dimensions
120mm X 76mm X 17mm
- Weight
84 grams
- Operating Temperature
0°C to 70°C

With the Presco system the door controller and keypad are separated, allowing the controller to do the code processing in remote protected environment. The code is transmitted from the keypad using only two wires, making installation simple and cost effective. The door controller and keypad can be separated by up to 1 kilometre using low cost non-shielded cable!



Distributed By:

Comtel Technologies Pty Ltd
1/1 Culverlands St, Heidelberg West VIC 3081
P: (03) 9457 4488 F: (03) 9457 4455
E: sales@comteltechnologies.com.au
W: www.comteltechnologies.com.au

Manufactured by:

Nidac Security P/L
2 Cromwell Street, Burwood, Vic 3125 Australia
ph + 61 3 9808 6244 fx + 61 3 9808 9335
www.nidac.com email: sales@nidac.com

